
List Of Port Numbers In Networking

*List Of Port
Numbers In
Networking*

*Downloaded from
www.everybodystreet.com
by Finn & Phelps*

UNDERSTANDING THE LIST OF PORT NUMBERS IN NETWORKING: A COMPLETE REFERENCE GUIDE

When you send an email, browse a website, or stream a video, an invisible system of digital doors opens and closes to make that connection possible. These doors are known as port numbers, and they are fundamental to how data travels across networks. Without a structured list of port numbers in

networking, the internet as we know it would descend into chaos, with traffic unable to find its intended destination. Understanding this system is essential for IT professionals, network administrators, cybersecurity specialists, and anyone who wants to deepen their knowledge of how digital communication actually works.

Port numbers serve as logical endpoints within a network connection. Think of an IP address as the street address of a building, while port numbers are the

individual apartment numbers inside that building. When data packets arrive at a server, the port number tells the system which service or application should receive that information. This layered addressing system allows a single device to handle multiple types of network traffic simultaneously without confusion.

WHAT ARE PORT NUMBERS AND HOW DO THEY WORK?

A port number is a 16-bit unsigned integer ranging from 0 to 65535. When combined with an IP address, it creates a unique socket that identifies a specific process or service on a device. This

combination, often written as **IP:Port** (for example, 192.168.1.1:80), provides the complete addressing information needed for network communication.

The Internet Assigned Numbers Authority (IANA) oversees the assignment of port numbers to ensure consistency across the global internet. The list of port numbers in networking is divided into three distinct ranges, each serving a different purpose in the network communication ecosystem.

The Three

Port Number Ranges

Well-Known Ports

(0-1023): These are reserved for system services and widely used protocols. Only system processes or privileged users can bind to these ports on most operating systems. This security measure prevents unauthorized applications from impersonating critical services.

Registered Ports

(1024-49151): IANA assigns these ports to user applications and specific services upon request. Companies often register ports for their proprietary software to avoid

conflicts with other applications.

Dynamic or Private Ports

(49152-65535):

These are available for temporary use by client applications. When your browser connects to a web server, the operating system typically assigns a random port from this range for the outbound connection.

ESSENTIAL WELL-KNOWN PORTS YOU SHOULD KNOW

A comprehensive list of port numbers in networking must begin with the well-known ports that form the backbone of internet services. These ports are standardized across all systems, ensuring universal compatibility.

- **Port 20 and 21 (TCP): FTP** – File Transfer Protocol uses port 20 for data transfer and port 21 for control commands. Despite being one of the oldest protocols still in use, FTP remains relevant for transferring large files, though its lack of encryption makes it a security concern in modern networks.
- **Port 22 (TCP): SSH** – Secure Shell provides encrypted remote administration capabilities. System administrators rely on port 22 for secure command-line access to servers, making it one of the most commonly targeted ports by attackers.
- **Port 23 (TCP): Telnet** – An unencrypted remote access protocol that transmits all data including passwords in plain text. Security best practices strongly discourage using Telnet in favor of SSH.
- **Port 25 (TCP): SMTP** – Simple Mail Transfer Protocol handles email transmission between mail servers. This port is essential for the email

delivery chain and is frequently monitored to prevent spam relay attacks.

- **Port 53 (UDP and TCP): DNS**
– Domain Name System translates human-readable domain names into IP addresses. This is arguably one of the most critical ports in the entire list of port numbers in networking, as virtually every internet interaction depends on DNS resolution.
- **Port 80 (TCP): HTTP** – Hypertext Transfer Protocol serves web pages from servers to browsers. Every

website you visit initially connects through port 80 before potentially being redirected to a secure connection.

- **Port 110 (TCP): POP3** – Post Office Protocol version 3 retrieves email from mail servers. Unlike IMAP, POP3 typically downloads messages to the client device and removes them from the server.
- **Port 143 (TCP): IMAP** – Internet Message Access Protocol allows email clients to access messages stored on a mail server. IMAP keeps messages on the server,

enabling access from multiple devices.

- **Port 443 (TCP): HTTPS** – HTTP over TLS/SSL provides encrypted web browsing. This port handles secure connections for online banking, e-commerce, and any service requiring data privacy.
- **Port 445 (TCP): SMB** – Server Message Block is used for file sharing, printer sharing, and other network communication in Windows environments. The infamous WannaCry ransomware attack exploited vulnerabilities in

SMB traffic on this port.

- **Port 993 (TCP): IMAPS** – Secure IMAP using SSL/TLS encryption for email retrieval. This provides a protected channel for accessing email messages over untrusted networks.
- **Port 995 (TCP): POP3S** – Secure POP3 using SSL/TLS encryption for email retrieval. Similar to IMAPS, this port ensures encrypted communication when downloading email.
- **Port 3389 (TCP): RDP** – Remote Desktop Protocol allows

remote graphical access to Windows systems. This port is heavily targeted for brute-force attacks and should be protected with strong authentication or VPN requirements.

COMMON REGISTERED PORTS AND THEIR APPLICATIONS

While well-known ports cover the fundamental internet services, registered ports extend the list of port numbers in networking to accommodate specialized applications and enterprise software.

- **Port 1433 (TCP):**

Microsoft SQL

Server – The default port for Microsoft's database management system. Database administrators configure firewalls to allow traffic to this port for client connections.

- **Port 1521 (TCP): Oracle Database** – Oracle's default listener port for client connections. Enterprise applications often require this port to be open for database access.
- **Port 2049 (UDP and TCP): NFS** – Network File System enables file sharing

across Unix-like systems.

Originally developed by Sun Microsystems,

NFS remains popular in Linux environments.

- **Port 3306**

(TCP): MySQL –

The default port for the MySQL database server. Web applications using LAMP stacks commonly rely on this port for database communication.

- **Port 3389**

(TCP): RDP –

Remote Desktop Protocol enables graphical remote access to Windows systems.

- **Port 5432**

(TCP):

PostgreSQL –

The default port

for the

PostgreSQL

database

management

system. This

open-source

database uses

this port for

client-server

communication.

- **Port 5900**

(TCP): VNC –

Virtual Network

Computing

provides remote

desktop

functionality

across multiple

operating

systems. VNC is

platform-

independent but

lacks the

encryption found

in RDP or SSH.

- **Port 8080**

(TCP): HTTP

Alternative –

Often used for

web proxy

servers and

development

environments.
Many application servers like Apache Tomcat and Jetty use port 8080 instead of the privileged port 80.

- **Port 8443 (TCP): HTTPS Alternative** – A common alternative to port 443 for secure web services, frequently used by web management interfaces and development environments.
- **Port 27017 (TCP): MongoDB** – The default port for MongoDB database instances. As NoSQL databases gain popularity,

understanding this port becomes increasingly important.

PORT NUMBERS FOR EMAIL SERVICES

Email remains a foundational internet service, and the list of port numbers in networking includes several ports dedicated to email delivery, retrieval, and management.

- **Port 25 (TCP): SMTP** – Standard email submission between mail servers. Many ISPs and cloud providers block outbound port 25 traffic to prevent spam, requiring users to submit email through designated

- submission ports.
- **Port 465 (TCP): SMTPS** – SMTP over SSL, providing encrypted email submission. This port was originally registered for SMTPS but has a complex history with different implementations.
 - **Port 587 (TCP): SMTP Submission** – The modern port for authenticated email submission from clients to servers. Most email providers require using this port with STARTTLS for secure email sending.
 - **Port 2525 (TCP): Alternate SMTP** – An unofficial

but commonly used port for SMTP submission when port 587 is blocked. Many email services support this as a fallback option.

UNDERSTANDING UDP PORTS VERSUS TCP PORTS

When examining any list of port numbers in networking, it is crucial to understand that port numbers work with both TCP and UDP protocols. The same port number can serve different services depending on whether it uses TCP or UDP, though in practice many services use one protocol exclusively.

TCP (Transmission Control Protocol) ports provide reliable, connection-oriented

communication. Services like web browsing, email, and file transfers use TCP because they require guaranteed delivery of data in the correct order. When you visit a website, TCP ensures that every byte of the webpage arrives intact.

UDP (User Datagram Protocol) ports offer faster, connectionless communication without delivery guarantees. Streaming services, online gaming, DNS queries, and Voice over IP (VoIP) applications frequently use UDP because they prioritize speed over perfect reliability. A few missing packets in a video stream cause a brief glitch, while waiting for retransmission would disrupt the entire viewing experience.

Understanding this

distinction helps network administrators configure firewalls more effectively and troubleshoot connectivity issues with greater precision.

SECURITY CONSIDERATIONS FOR PORT MANAGEMENT

Managing port security is a critical responsibility for any network professional. An open port is a potential entry point for attackers, and understanding the complete list of port numbers in networking helps identify which ports should be accessible and which should remain closed.

Port

Scanning Firewall and Configura Vulnerability Best Practices Assessment

nt

Attackers commonly use port scanning tools to identify open ports on target systems. Services running on unexpected ports or insecure protocols present opportunities for exploitation. Regular port scanning of your own network helps identify misconfigurations and unauthorized services before attackers discover them.

Effective firewall management follows the principle of least privilege: only necessary ports should be open, and only to authorized IP addresses whenever possible. For example, if your organization does not run a public web server, port 80 and 443 should be blocked at the network perimeter.

Port

Knocking and Obfuscati on

Some organizations implement port knocking, a technique where ports remain closed until a specific sequence of connection attempts occurs. This adds a layer of obscurity to security, though it should never replace proper authentication and encryption.

Common security-critical ports to monitor include:

- Port 22 (SSH) – Monitor for brute-force login attempts
- Port 3389 (RDP)

– Extremely common target for automated attacks

- Port 445 (SMB) – Associated with ransomware and worm propagation
- Port 1433 (MSSQL) – Targeted for database exploitation
- Port 3306 (MySQL) – Frequently scanned for exposed database instances

PORT NUMBERS IN CLOUD AND VIRTUALIZED ENVIRONMENTS

Modern networking extends the traditional list of port numbers in networking into cloud platforms,

containerized applications, and virtualized infrastructure. Understanding how ports function in these environments is essential for contemporary network management.

Cloud Load Balancers often use port 80 and 443 for incoming traffic, then forward requests to backend services running on higher ports. This architecture allows multiple application instances to run on the same server without port conflicts.

Container Orchestration platforms like Kubernetes assign dynamic port numbers to containerized services, while providing stable port mappings through

service abstraction layers. Containers within a pod can communicate on any port, but external access requires explicit configuration.

Serverless Computing functions typically receive traffic through API gateways that manage port assignments automatically. Developers rarely need to concern themselves with port numbers in serverless architectures, as the platform handles routing transparently.

TROUBLESHOOTING PORT-RELATED CONNECTIVITY ISSUES

Even with a thorough understanding of the list of port numbers in networking, connectivity problems

arise. Here are practical steps for diagnosing and resolving port-related issues.

Checking Port Availability

y

Use commands like **netstat -an** on Windows or **ss -tln** on Linux to display all listening ports on a system. This reveals which services are actively waiting for connections and their current state