
How To Use A Ratchet Strap

*How To Use
A Ratchet
Strap*

*Downloaded from
www.everybodystreet.com
by Draven & Felipe*

MASTERING THE ART OF CARGO CONTROL: A COMPLETE GUIDE ON HOW TO USE A RATCHET STRAP

Picture this: you have just loaded your motorcycle onto a trailer for a weekend trip, or perhaps you have secured furniture in the back of a pickup truck after a long day of moving. The only thing standing between your precious cargo and the hard pavement is a length of webbing and a metal mechanism. For

millions of people around the world, the humble ratchet strap is the unsung hero of transportation, yet it is also one of the most misunderstood tools in everyday use. Knowing how to use a ratchet strap correctly is not just about convenience; it is about safety, legal compliance, and peace of mind. A strap that is improperly tensioned can loosen during transit, leading to damaged goods or, worse, a serious road hazard. Conversely, a strap that is routed or fastened incorrectly can damage the very

items you are trying to protect. Whether you are a seasoned truck driver, a weekend warrior with a utility trailer, or a DIY enthusiast hauling lumber from the hardware store, understanding the proper techniques for ratchet strap operation is an essential skill. This guide will walk you through everything you need to know, from the anatomy of the device to the step-by-step process of securing a load, along with critical safety tips and common pitfalls to avoid.

Understanding the

Anatomy of a Ratchet Strap

Before you can master the technique, it helps to understand what you are working with. A standard ratchet strap consists of three main components: the webbing, the ratchet mechanism, and the end fittings. The webbing is typically made of polyester, chosen for its high strength, low stretch, and resistance to UV damage and mildew. The ratchet mechanism is the heart of the tool, a metal assembly that uses a geared spool and a pawl to take up slack

and lock the webbing in place under tension. The end fittings, which can be hooks, loops, or flat hooks, attach to anchor points on your vehicle or trailer. There are also two distinct sides to the webbing: the fixed end, which is the shorter piece that attaches to the ratchet body, and the loose end, which is the long length that feeds through the ratchet. Understanding this distinction is crucial because mixing them up is one of the most common errors people make when learning how to use a ratchet strap. Additionally, ratchet straps come in various working load limits, often abbreviated as WLL. It is imperative to select a strap whose WLL meets or exceeds the weight of the cargo

you intend to secure. Using a strap that is too weak is a recipe for disaster, while using one that is excessively heavy duty may be impractical for lighter loads.

Preparing Your Equipment and Environment

A successful tie-down operation begins long before you pull the first length of webbing. Preparation is the foundation of safe cargo control. Start by inspecting your ratchet straps thoroughly. Look

for cuts, fraying, or abrasions on the webbing. Check the ratchet mechanism for rust, cracks, or deformities. Ensure that the springs and pawls move freely and that the release mechanism operates smoothly. Examine the hooks or end fittings for any signs of bending, cracking, or wear. A damaged strap should never be used; it is far cheaper to replace a strap than to deal with the consequences of a failure. Next, assess your cargo and your vehicle or trailer. Identify secure, robust anchor points. These are typically D-rings, stake pockets, or reinforced slots on the bed or frame of the vehicle. Avoid tying straps to bumpers, axles, or other

components that are not designed for tie-down forces. Also, consider the shape and fragility of your cargo. Sharp edges can cut webbing under tension, so use edge protectors made of rubber, plastic, or heavy fabric to shield the straps. Finally, ensure that your work area is safe. Park on a level surface, engage the parking brake, and chock the wheels if necessary. Rushing through preparation is a common mistake, and taking a few extra minutes here can save you hours of trouble later.

A Step-by-Step

Guide: How to Use a Ratchet Strap Correctly

Now that you have inspected your equipment and prepared your cargo area, it is time to put the strap into action. Follow these steps carefully to achieve a secure and balanced tie-down.

Step 1: Position the Strap and Attach the Fixed End. Unwind the entire length of webbing from the ratchet spool. Separate the fixed end from the

loose end. The fixed end is the shorter piece of webbing that is permanently sewn to the ratchet mechanism. Attach the hook or fitting on the fixed end to a suitable anchor point on one side of your vehicle or trailer. Ensure the hook is fully seated and oriented so that it cannot slip off under load. For flat hooks, make sure they are facing the correct direction and are positioned over a stable part of the anchor.

Step 2: Route the Webbing Over Your Cargo. Pull the loose end of the webbing across the top of your cargo. Keep the webbing flat and free of twists. A twisted strap will not lie flat against the cargo, reducing its holding

power and potentially damaging the webbing. Route the strap to the opposite anchor point on the vehicle. The webbing should contact the cargo at the widest or most stable point to prevent shifting.

Step 3: Attach the Loose End to the Opposite Anchor.

Attach the hook or fitting on the loose end to the anchor point on the opposite side of the vehicle. Ensure it is secure. At this point, the strap should be draped over the cargo but not yet tight. You want a reasonable amount of slack so that you can operate the ratchet mechanism.

Step 4: Open the Ratchet Mechanism.

This is a step that confuses many beginners. Locate the release lever on the

ratchet. Typically, you need to pull the release lever to unlock the ratchet, then flip the handle into the open or "load" position. On most ratchets, the handle will open to a position where it is roughly perpendicular to the body of the strap. In this position, the spool is free to rotate, and the pawls are disengaged. You may hear a clicking sound as you open it.

Step 5: Feed the Loose Webbing Through the Ratchet Spool.

Take the loose end of the webbing and insert it through the slot in the ratchet spool. Pull the webbing through until there is minimal slack. It is important to pull as much slack out of the system as possible by hand before you start cranking. The tighter

you get it by hand, the fewer ratchet strokes you will need, and the more evenly the tension will be applied. Ensure the webbing is lying flat and centered in the spool slot.

Step 6: Close the Ratchet and Begin Tensioning.

Once the webbing is fed through and you have pulled out the slack, close the ratchet handle back to its starting position. You should hear a clicking sound as the pawls engage the teeth on the spool. The ratchet is now in tensioning mode. Begin moving the handle back and forth. Each time you push the handle down, it takes up a small amount of webbing onto the spool. Each time you lift the handle, it resets for another pull. Continue this motion

until the strap is tight against the cargo. You should see the webbing become taut, and you will feel resistance in the handle.

Step 7: Check the Tension and Repeat.

Once the strap feels tight, give the handle a few extra clicks to ensure a secure hold. Be careful not to overtighten. Overtightening can damage cargo, induce stress fractures in equipment, or even break the webbing. A good rule of thumb is that the strap should be tight enough that you cannot easily deflect the webbing with your hand, but it should not be so tight that it distorts the cargo or feels like it is at its breaking point. For larger or heavier loads, repeat the process with

additional straps, positioning them at strategic intervals along the length of the cargo.

Step 8: Secure the Excess Webbing.

After tensioning, you will have a tail of excess webbing. This loose end can be a flapping hazard while driving. Wind it up neatly and secure it with a rubber band, a Velcro strap, or tuck it under itself in a way that prevents it from coming loose. Never cut the excess webbing, as this can cause the strap to unravel and will shorten its usable life.

Common Mistakes

to Avoid When Using a Ratchet Strap

Even experienced operators can fall into bad habits. Being aware of the most frequent errors will help you tie down your loads more safely and effectively. One of the most common mistakes is **webbing twist**. A twisted strap has reduced strength and can abrade against itself or the cargo. Always lay the webbing flat. Another frequent error is **incorrect routing through the ratchet**. If the webbing is not fed

through the spool slot properly, the ratchet may not engage correctly, or the webbing may jam. Always double-check the webbing path against the manufacturer's instructions.

Overtightening is also a major issue. While a secure load is the goal, applying excessive force can damage the cargo, the strap, or the anchor points. Use your judgment and stop when the strap is snug and the cargo is immobile. **Using the wrong type of anchor** is another critical error. Hooks should be fully seated over a solid part of the anchor, not just loosely hanging. Finally, a surprisingly common mistake is **forgetting to secure the excess**

webbing. A flapping strap tail can be distracting to other drivers and can even cause injury or damage if it gets caught in moving parts.

Safety Tips and Best Practices for Ratchet Strap Usage

Safety should always be your primary concern when securing a load. Here are some essential guidelines to follow every time you

use a ratchet strap. First, always adhere to the **Working Load Limit (WLL)** and **breaking strength** of your straps. The WLL is the maximum safe load the strap is designed to hold in a straight pull. Never exceed this limit. For overhead lifting applications, ensure the strap is rated for lifting and that you are using appropriate hardware. Second, use **edge protectors** whenever your cargo has sharp corners or abrasive surfaces. A simple edge protector can prevent a cut that could lead to strap failure. Third, regularly **inspect your straps** before and after each use. Look for signs of wear, UV damage, chemical exposure, and fraying. Keep a log of inspections for

commercial applications. Fourth, ensure that your **anchor points** are rated for the load you are securing. A weak anchor point can fail even if the strap is perfect. Fifth, never use a strap that has been **knotted** to shorten it. Knots reduce the strength of the webbing by up to 50 percent and create stress points. Instead, use a longer strap and adjust the routing, or use a different tie-down method. Sixth, be mindful of **weather conditions**. Extreme heat can degrade webbing over time, and freezing temperatures can make mechanisms stiff. Finally, always **recheck your straps** after driving a short distance. Loads can shift and straps can

loosen as the vehicle settles. A quick stop after 10 or 15 minutes to retighten is a good habit to develop.

Maintenance and Storage for Long-Lasting Straps

Your ratchet straps are an investment, and proper care will extend their life significantly. After each use, particularly if you have been driving in wet, salty, or muddy conditions, clean the webbing with mild soap and water. Rinse thoroughly and allow

the strap to dry completely before storing. Never store wet webbing, as it can promote mildew growth and weaken the fibers. The ratchet mechanism should be kept clean and lightly lubricated with a silicone-based spray or a light machine oil. This prevents rust and keeps the moving parts operating smoothly. Store your straps in a cool, dry place, away from direct sunlight. UV radiation is one of the primary enemies of polyester webbing, causing it to become brittle and lose strength over time. Coiling the webbing neatly and storing it in a bag or a dedicated storage box will prevent tangling and protect it from dirt and debris. Avoid hanging straps on metal hooks

where the webbing can rub against rough
edges