

---

# Oracle PL SQL For Dummies

---

Downloaded from  
Oracle PL SQL [www.everybodystreet.com](http://www.everybodystreet.com)  
For Dummies by Williams & Nathan

---

## INTRODUCTION: WHAT IS ORACLE PL/SQL AND WHY SHOULD YOU LEARN IT?

---

If you are new to database programming, you have probably heard of Oracle SQL - the standard language for querying and manipulating data in Oracle databases. But there is a more powerful tool that builds on SQL: Oracle PL/SQL. PL/SQL stands for **Procedural Language extension to SQL**. Think of SQL

as a way to ask questions or give commands to the database ("Give me all customers from New York"), while PL/SQL allows you to write full programs with logic, loops, conditions, and error handling. It is like moving from giving single instructions to writing a complete recipe. This beginner's guide to Oracle PL/SQL will explain the fundamentals in plain English, just like a "for dummies" introduction, but without the jargon overload.

Learning PL/SQL opens the door to creating robust database

applications, automating repetitive tasks, and building efficient business logic right inside the database. Whether you are a student, a data analyst, or a developer switching to Oracle, understanding PL/SQL basics is a valuable skill. In this article, we will walk through the essential concepts, set up a simple environment, and write your first PL/SQL block. By the end, you will have the confidence to start experimenting on your own.

---

## UNDERSTANDING THE BASICS OF ORACLE PL/SQL

---

# What Is

# PL/SQL Exactly?

PL/SQL is Oracle's proprietary procedural language. It combines the data manipulation power of SQL with procedural constructs found in languages like Pascal or C. A PL/SQL program is called a **block**, which consists of three sections: declaration, executable, and exception handling. You do not need to use all three, but the executable section is mandatory. Blocks can be anonymous (run once) or stored in the database as procedures, functions, or packages.

For example, you can write a block that takes a department ID, loops through all employees

in that department, calculates a bonus, and updates the salary – all in one piece of code that runs on the database server. This reduces network traffic and improves performance.

## Key Differences Between SQL and PL/SQL

To appreciate PL/SQL, it helps to understand where SQL ends and PL/SQL begins:

- **SQL is set-based:** You operate on entire sets of rows
- **SQL has limited logic:** You cannot write IF conditions across multiple steps easily. PL/SQL includes conditional statements, loops, and variables.
- **SQL cannot handle exceptions gracefully:** In PL/SQL, you can catch errors and take corrective actions.
- **PL/SQL runs on the server:** This means you can build application

(e.g., UPDATE all employees in a department).

PL/SQL is procedural – you can navigate row by row using loops and cursors.

logic close to the data, which can be faster than fetching data to a client program.

For a beginner, the main takeaway is that PL/SQL lets you write programs that combine SQL queries with procedural logic, all stored and executed inside the Oracle database.

---

## SETTING UP YOUR ENVIRONMENT

---

# Installing Oracle Database and SQL\*Plus

## (or Use Oracle Live SQL)

The best way to start learning PL/SQL is to have a practice environment. You can download the free Oracle Database Express Edition (XE) and install it on your computer. It also includes SQL\*Plus, a command-line tool for running SQL and PL/SQL statements. However, installation can be heavy for some beginners. A lighter alternative is **Oracle Live SQL** ([livesql.oracle.com](https://livesql.oracle.com)), a free web-based tool that lets you write and run PL/SQL code without any installation. I recommend Live SQL

for the first few steps.

Once you have access, open the SQL worksheet (or SQL\*Plus) and get ready to type your first PL/SQL code.

## Your First PL/SQL Block: Hello World

In PL/SQL, the classic “Hello World” program looks like this:

```
BEGIN
DBMS_OUTPUT.PUT_L
INE('Hello,
PL/SQL World!');
END;
```

To see the output, you must enable server output by typing `SET SERVEROUTPUT ON;`

before running the block (in SQL\*Plus) or use the output panel in Live SQL. This simple example shows the structure: `BEGIN` starts the executable section, and `END;` terminates it. The `DBMS_OUTPUT.PUT_LINE` procedure prints a message. Congratulations – you have just written a PL/SQL program!

---

### CORE PL/SQL CONCEPTS FOR BEGINNERS

---

## Variables and Data Types

Variables allow you to store data temporarily. You declare them in the **DECLARE** section (optional if you don't

need variables). Common data types include NUMBER, VARCHAR2, DATE, and BOOLEAN. Example:

```
DECLARE
    v_employee_name
    VARCHAR2(100);
    v_salary
    NUMBER(8,2);
    v_hire_date
    DATE;
BEGIN
    -- assign values
    v_employee_name :=
    'John Doe';
    v_salary := 50000;
    v_hire_date :=
    SYSDATE;
    DBMS_OUTPUT.PUT_LINE(
    'Employee: ' ||
    v_employee_name);
END;
```

You can also use the %TYPE attribute to declare a variable with the same data type as a table column, which makes your code more robust.

## Control Structures: IF-THEN and Loops

PL/SQL supports standard control structures. The IF statement checks conditions:

```
IF v_salary > 100000
THEN
    DBMS_OUTPUT.PUT_LINE(
    'High earner');
ELSIF v_salary >
50000 THEN
    DBMS_OUTPUT.PUT_LINE(
    'Medium earner');
ELSE
    DBMS_OUTPUT.PUT_LINE(
    'Entry level');
END IF;
```

Loops come in three flavors: BASIC LOOP, FOR LOOP, and WHILE LOOP. The FOR LOOP is

easiest for beginners:

```
BEGIN
  FOR i IN 1..10
  LOOP
    DBMS_OUTPUT.PUT_LINE(
      'Loop iteration: ' ||
      i);
  END LOOP;
END;
```

These constructs let you build real logic, such as processing multiple records.

## Cursors: Handling Query Results

When your SQL query returns multiple rows, you need a **cursor** to loop through them. An explicit cursor is declared in the `DECLARE` section, opened in the `BEGIN` section, and rows are

fetches one by one.  
Example:

```
DECLARE
  CURSOR emp_cursor
  IS
    SELECT
      employee_id,
      last_name FROM
      employees WHERE
      department_id = 50;
  v_id
  employees.employee_id
  %TYPE;
  v_name
  employees.last_name%T
  YPE;
BEGIN
  OPEN emp_cursor;
  LOOP
    FETCH
    emp_cursor INTO v_id,
    v_name;
    EXIT WHEN
    emp_cursor%NOTFOUND;
    DBMS_OUTPUT.PUT_LINE(
    v_id || ' - ' ||
    v_name);
  END LOOP;
  CLOSE emp_cursor;
END;
```

This is a fundamental pattern: declare a cursor with your query, fetch rows into variables, process them, and exit when

no more rows exist. For beginners, using a cursor FOR loop (implicit cursor) is even simpler because Oracle handles opening, fetching, and closing automatically:

```
BEGIN
  FOR emp_rec IN
    (SELECT employee_id,
     last_name FROM
     employees WHERE
     department_id = 50)
  LOOP
    DBMS_OUTPUT.PUT_LINE(
      emp_rec.employee_id ||
      ' - ' ||
      emp_rec.last_name);
  END LOOP;
END;
```

---

## WORKING WITH PROCEDURES AND FUNCTIONS

---

# Creating a Simple

# Stored Procedur e

Anonymous blocks are fine for one-time tests, but real applications use stored procedures that reside in the database. A procedure is a named PL/SQL block that can accept parameters. Here is a simple example that updates an employee's salary:

```
CREATE OR REPLACE
PROCEDURE
raise_salary (
  p_employee_id IN
  employees.employee_id
  %TYPE,
  p_percent      IN
  NUMBER
) IS
BEGIN
  UPDATE employees
  SET salary =
  salary * (1 +
  p_percent/100)
```

```

        WHERE employee_id
      = p_employee_id;
      COMMIT;
      DBMS_OUTPUT.PUT_LINE(
        'Salary raised.');
```

To call this procedure from another block or tool:

```

EXECUTE
raise_salary(101,
10);
```

## Functions vs Procedures

Functions are similar to procedures but they **return a value**. Use functions when you need to compute something and use the result in a SQL statement. For example, a function to calculate annual

bonus:

```

CREATE OR REPLACE
FUNCTION
calculate_bonus (
  p_salary IN NUMBER
) RETURN NUMBER IS
  v_bonus NUMBER;
BEGIN
  IF p_salary <
50000 THEN
    v_bonus :=
p_salary * 0.10;
  ELSE
    v_bonus :=
p_salary * 0.05;
  END IF;
  RETURN v_bonus;
END calculate_bonus;
```

You can call it in a SELECT statement:

```

SELECT
employee_id,
calculate_bonus(s
alary) FROM
employees;
```

Understanding when to use a procedure (for actions) versus a function (for computations) is an important part of learning PL/SQL best practices.

## ERROR HANDLING IN PL/SQL

# Exceptions and Exception Handlers

No program is perfect, and database operations can fail. PL/SQL provides a robust exception handling mechanism. The exception section comes after the executable section. You can catch predefined exceptions (like `NO_DATA_FOUND`, `TOO_MANY_ROWS`) or define your own.

```
BEGIN
    UPDATE employees
SET salary = 100000
WHERE employee_id =
99999;
```

```
IF SQL%ROWCOUNT =
0 THEN
    RAISE_APPLICATION_ERR
OR(-20001, 'Employee
not found');
    END IF;
EXCEPTION
    WHEN NO_DATA_FOUND
THEN
    DBMS_OUTPUT.PUT_LINE(
'No employee with
that ID.');
```

```
    WHEN OTHERS THEN
    DBMS_OUTPUT.PUT_LINE(
'Error: ' ||
SQLERRM);
END;
```

Using `WHEN OTHERS` as a catch-all is common, but you should log or handle specific exceptions for better control. Good error handling makes your PL/SQL programs more reliable and easier to debug.

## PRACTICAL TIPS FOR LEARNING PL/SQL

# Practice with Sample Queries

The best way to learn is by doing. Start with the sample schema that comes with Oracle (HR schema - employees, departments). Write small anonymous blocks to practice variable assignment, loops, and cursors.

Then move to creating procedures and functions. Gradually add error handling. Use Oracle Live SQL to experiment without risk.

## Common Mistakes to Avoid

- **Forgetting SET SERVEROUTPUT ON:** Without it, you won't see output from DBMS\_OUTPUT.